

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 May 2004 (27.05.2004)

PCT

(10) International Publication Number
WO 2004/043941 A1

(51) International Patent Classification⁷: C07D 301/12,
303/04

(21) International Application Number:
PCT/EP2003/012519

(22) International Filing Date:
10 November 2003 (10.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02/14206 12 November 2002 (12.11.2002) FR

(71) Applicant (for all designated States except US): SOLVAY
(SOCIÉTÉ ANONYME) [BE/BE]; Rue du Prince Albert,
33, B-1050 Brussels (BE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): STREBELLE,
Michel [BE/BE]; Rue Sombre, 84, B-1150 Brussels (BE).
CATINAT, Jean-Pierre [BE/BE]; Rue de la Résistance,
93, B-7131 Waudrez (BE).

(74) Agents: VANDE GUCHT, Anne et al.; Solvay (Société
Anonyme), Intellectual Property Department, Rue de Rans-
beek, 310, B-1120 Brussels (BE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted
a patent (Rule 4.17(ii)) for the following designations AE,
AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH,
CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES,
FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT,
TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent
(BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- as to the applicant's entitlement to claim the priority of the
earlier application (Rule 4.17(iii)) for the following desig-
nation US
- as to the applicant's entitlement to claim the priority of the
earlier application (Rule 4.17(iii)) for the following desig-
nation US
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: PROCESS FOR THE MANUFACTURE OF 1,2-EPOXY-3-CHLOROPROPANE

(57) Abstract: Process for the manufacture of 1,2-epoxy-3-chloropropane by reaction between allyl chloride and hydrogen peroxide in the presence of a catalyst and in the possible presence of at least one solvent, in which the allyl chloride employed comprises less than 2000 ppm by weight of 1,5-hexadiene.

WO 2004/043941 A1

Process for the manufacture of 1,2-epoxy-3-chloropropane

The invention relates to a process for the manufacture of 1,2-epoxy-3-chloropropane by reaction between allyl chloride and hydrogen peroxide.

It is known to manufacture 1,2-epoxy-3-chloropropane (or
5 epichlorohydrin) by epoxidation of allyl chloride by means of hydrogen peroxide in the presence of methanol as solvent and in the presence of a catalyst comprising TS-1, as disclosed in United States Patent US 6 350 888.

This known process exhibits the disadvantage that the catalyst rapidly deactivates, sometimes after a few hours of operation. This necessitates, in a
10 continuous industrial process, frequent shutdowns in order to separate the catalyst from the epoxidation medium and to replace it by fresh catalyst or by regenerated catalyst. These operations significantly increase the cost of the process.

The present invention is targeted at overcoming this disadvantage by
15 providing a novel process in which the deactivation is greatly reduced without, however, reducing the activity of the catalyst (or the degree of conversion of the reactants, or the rate of the epoxidation reaction) and the selectivity of the epoxidation reaction.

The invention consequently relates to a process for the manufacture of 1,2-
20 epoxy-3-chloropropane by reaction between allyl chloride and hydrogen peroxide in the presence of a catalyst and in the possible presence of at least one solvent, in which the allyl chloride employed comprises less than 2000 ppm by weight of 1,5-hexadiene.

One of the essential characteristics of the invention lies in the purity of the
25 allyl chloride employed in the process. This is because it has been found that the use of purified allyl chloride makes it possible to increase the duration of use of the catalyst (and thus to reduce the frequency with which the catalyst has to be removed from the epoxidation medium in order to be replaced) while retaining a high activity and a high selectivity.

30 The purified allyl chloride employed in the process of the invention can be obtained by any appropriate known means, for example by chlorination, as disclosed in International Application WO 96/03362. The purification can also be carried out by distillation.

The purified allyl chloride employed in the process of the invention generally comprises an amount of 1,5-hexadiene of less than or equal to 1500 ppm by weight, in particular of less than or equal to 1000 ppm by weight and preferably of less than or equal to 500 ppm by weight; values of less than or equal to 400 ppm by weight and in particular of less than or equal to 300 ppm are the most advantageous, for example values of less than 200 ppm. The amount of 1,5-hexadiene present in the purified allyl chloride is usually greater than or equal to 1 ppm by weight, most frequently greater than or equal to 10 ppm by weight.

Without being committed to a scientific theory, the Applicant Company believes that the 1,5-hexadiene is responsible at least in part for the problem of the deactivation of the catalyst. This might be explained by the fact that 1,5-hexadiene would also react with the hydrogen peroxide in the presence of the catalyst and would thus form heavy byproducts, for example products with the empirical formula $C_7H_{14}O_3$. This family of products would result from the double epoxidation and from the partial methanolysis of the 1,5-hexadiene, when methanol is used as solvent. The product concerned can, for example, be 1,2-epoxy-5-hydroxy-6-methoxyhexane. These heavy products might have the effect of blocking the pores of the catalyst and thus of reducing its activity.

The epoxidation medium in which the epoxidation reaction of the process according to the invention takes place generally comprises a liquid phase, comprising allyl chloride, hydrogen peroxide, the solvent, the 1,2-epoxy-3-chloropropane formed and optionally byproducts, and a solid phase comprising the catalyst. The liquid phase of the epoxidation medium also generally comprises water, typically in a concentration of 5 to 25% by weight. In an alternative form, the epoxidation medium can comprise 2 liquid phases, one essentially aqueous and one essentially organic.

In the process according to the invention, the hydrogen peroxide is advantageously employed in the form of an aqueous solution. The aqueous solution generally comprises at least 10% by weight of hydrogen peroxide, in particular at least 20% by weight. It usually comprises at most 70% by weight of hydrogen peroxide, in particular 50% by weight.

Generally, the molar ratio of the amount of allyl chloride employed to the amount of hydrogen peroxide employed is greater than or equal to 0.1, in particular greater than or equal to 0.5 and preferably greater than or equal to 1. This ratio is usually less than or equal to 100, more especially less than or equal

to 50, generally less than or equal to 25. In a particularly advantageous alternative form of the process according to the invention, use is made of an excess of allyl chloride so that the molar ratio of the amount of allyl chloride employed to the amount of hydrogen peroxide employed is greater than or equal to 2, in particular greater than or equal to 3, very particularly greater than or equal to 4. In this advantageous alternative form, the ratio is generally less than or equal to 10, more especially less than or equal to 8 and usually less than or equal to 7. A ratio of approximately 5 is particularly well suited. The use of an excess of allyl chloride in this alternative form makes it possible to obtain an even greater increase in the selectivity (and therefore a reduction in the formation of undesirable byproducts) and, in combination with the purified allyl chloride, makes it possible to also obtain a reduction in the deactivation of the catalyst.

The solvent used in the process according to the invention can be chosen from any organic solvent which is at least partially soluble in water, and their mixtures. Solvents which are particularly suitable are alcohols. The preferred alcohols comprise from 1 to 5 carbon atoms. Those which comprise a single -OH group are highly suitable. Mention may be made, as examples, of methanol, ethanol, n-propanol, isopropanol, (tert-)butanol and pentanol. Generally, it is methanol or tert-butanol. Methanol is the commonest.

When the epoxidation medium comprises only a single liquid phase, the latter generally comprises at least 30% by weight of solvent, in particular at least 50% by weight. This amount is usually at most 90% by weight, more especially at most 75% by weight. When the epoxidation medium comprises two liquid phases, the epoxidation medium can comprise less solvent and may even be devoid of solvent.

The catalyst used in the process according to the invention generally comprises a zeolite, namely a solid comprising silica which exhibits a microporous crystalline structure. The zeolite is advantageously devoid of aluminium. It preferably comprises titanium.

The zeolite which can be used in the process according to the invention can have a crystalline structure of ZSM-5, ZSM-11 or MCM-41 type or of zeolite beta type. Zeolites of ZSM-5 type are highly suitable. Those exhibiting an infrared absorption band at approximately $950\text{-}960\text{ cm}^{-1}$ are preferred.

The zeolites which are particularly well suited are the titanium silicalites. Those corresponding to the formula $x\text{TiO}_2(1-x)\text{SiO}_2$ in which x is from 0.0001 to 0.5, preferably from 0.001 to 0.05, and exhibiting a crystalline structure of ZSM-

5 type give particularly favourable results. Such zeolites are generally known under the name TS-1.

The catalyst is advantageously provided in the form of spherical particles obtained by any known method. A method which is particularly well suited is
5 that disclosed in International Application WO 99/24164 from Solvay (Société Anonyme). The catalyst can also be provided in the form of non-spherical particles obtained, for example, by extrusion as disclosed in International Application WO 99/28029 from Solvay (Société Anonyme).

The catalyst particles generally exhibit a mean diameter of greater than or
10 equal to 0.01 mm and less than or equal to 5 mm, a specific surface of greater than or equal to 1 m²/g and less than or equal to 900 m²/g (determined according to the nitrogen adsorption method), a bulk density of between 0.1 and 1.0 g/ml, a pore volume of between 0.15 and 2.5 ml/g and a distribution of the diameters of the pores with a maximum of between 15 and 2000 Å.

15 The catalyst can be present in the process according to the invention in the form of a bed. It can be a stationary bed or a fluid bed. A fluid bed is preferred.

The epoxidation reaction of the process according to the invention can be carried out in any type of appropriate reactor. It can, for example, be a
single-pass bed. It can also be a reactor of loop type comprising recirculation of
20 the epoxidation medium, with or without recirculation of the catalyst.

The temperature at which the epoxidation reaction can be carried out is generally greater than or equal to 0°C, in particular greater than or equal to 35°C, more particularly greater than or equal to 45°C and preferably greater than or equal to 55°C. The temperature is usually less than or equal to 120°C, more
25 especially less than or equal to 100°C, generally less than or equal to 80°C, temperatures of less than or equal to 65°C giving highly satisfactory results. When the temperature is from 45 to 80°C, the advantage is observed, in comparison with a lower temperature, for example of approximately 35°C, that the rate of deactivation of the catalyst is also reduced.

30 In the process according to the invention, it may furthermore prove to be advantageous to maintain the pH of the liquid phase of the epoxidation medium during the epoxidation at a selected value. The latter corresponds, during a measurement carried out at ambient temperature with a Metrohm® 6.0239.100 electrode (electrolyte 3M KCl) on a withdrawn sample of the epoxidation
35 medium, to values of greater than or equal to 1.5, in particular of greater than or equal to 3, more particularly of greater than or equal to 3.2. The pH is

advantageously maintained at a value of less than or equal to 5, more especially of less than or equal to 4.8, values of less than or equal to 4.5 giving good results. When the pH is maintained at a value of greater than or equal to 3 and of less than or equal to 4.5, the advantage is observed, in comparison with a process
5 carried out at natural pH without control of the pH, that the selectivity is higher without a reduction in the activity.

The pH can be controlled by addition of a base or of a mixture of a salt and of its conjugate base or acid. The base can be chosen from water-soluble bases. They can be strong bases or weak bases. Mention may be made, as examples, of
10 an alkali metal or alkaline earth metal hydroxide, carbonate or acetate. Sodium hydroxide is preferred.

The process of the invention can be carried out at any pressure. The epoxidation medium may, if appropriate, be composed of a liquid at boiling point.

15 The process according to the invention can be carried out continuously or batchwise.

Examples

The tests were carried out in a plant composed essentially of a tubular reactor, jacketed under pressure, in a liquid-solid fluidized bed (diam.: 1.5 cm, h:
20 50 cm), with a recirculation loop. The loop comprises in particular a reflux condenser, at atmospheric pressure, positioned directly at the outlet of the reactor (condensation of the allyl chloride), and a pH probe, making it possible to regulate the pH. The overall volume of the plant was approximately 350 ml.

The temperature of the reactor was regulated using a cryothermostat.

25 The pressure in the reactor was regulated at 4.5 bar using a pneumatic valve.

The epoxidation medium was reduced in pressure from its exit from the reactor and the liquid-gas mixture resulting therefrom was cooled by passing into a jacketed glass coil. The set point of the cryothermostat was fixed at -20°C.

30 The liquid phase was divided into two streams at the outlet of the condenser:

- the liquid outflow, the flow rate of which corresponded to that of the reactant feeds,
- and a second greater outflow, which formed the recirculation stream. The

35 H₂O₂, allyl chloride (ALC) and methanol (CH₃OH) feeds were added to this

recirculation stream. It is also at this level that the system for measuring and regulating the pH was situated.

Movement towards the reactor was provided by a membrane pump. The recirculation flow rate was measured using a flow meter and was adjusted to 5 l/h. Before entering the reactor, the liquid passed through a preheater.

Use was made, in these tests, of 18.6 g of a catalyst (i.e. 6.5 g of TS-1) provided in the form of 0.4 - 0.6 mm beads composed of Ti silicalite (35 weight%) dispersed in a microporous silica matrix (65 weight%). They were prepared according to a sol-gel process in the presence of a gas phase [as disclosed in WO 99/24164 from Solvay (Société Anonyme)].

The feed flow rates corresponding to the two types of epoxidation medium used are shown below.

Epoxidation medium 1:

ALC/H₂O₂ : 2 mol/mol

15 CH₃OH/ALC : 7.8 mol/mol

ALC : 38.2 ml/h

CH₃OH : 148.2 ml/h

39 weight% H₂O₂ : 20.5 g/h

Epoxidation medium 2:

20 ALC/H₂O₂ : 5 mol/mol

CH₃OH/ALC : 2.1 mol/mol

ALC : 95.5 ml/h

CH₃OH : 99.7 ml/h

39 weight% H₂O₂ : 20.5 g/h

25 The degree of conversion (DC) of the H₂O₂ was calculated from the inlet and outlet flow rates of the H₂O₂, the latter being determined using the results of the iodometric assay of the residual H₂O₂ in the overflow liquid, according to the following formula:

DC (%) = 100 × (H₂O₂ employed in mol/h – unconverted H₂O₂ in mol/h)/H₂O₂ employed in mol/h, in which unconverted H₂O₂ = concentration of H₂O₂ in the overflow in mol/kg × overflow flow rate in kg/h.

The term "C3 formed" is understood to denote, in the text which follows, epichlorohydrin (EPI) and the various byproducts resulting from the opening of the oxirane ring, namely 1-chloro-3-methoxy-2-propanol (recorded as 35

1C3OMe2Pol), 1-chloro-2-methoxy-3-propanol (recorded as 1C2OMe3Pol), 3-chloro-1,2-propanediol (MCG) and 1,3-dichloro-2-propanol (1,3DCPol).

The EPI/C3 formed selectivity can thus be calculated, from the chromatogram obtained by vapour-phase chromatography of the liquid outflow, using the expression:

$$\text{EPI/C3f selectivity (\%)} = 100 \times \text{EPI}_{\text{formed in mol/h}} / \Sigma (\text{EPI} + 1\text{C3OMe2Pol} + 1\text{C2OMe3Pol} + \text{MCG} + 1,3\text{DCPol})_{\text{formed in mol/h}}$$

Examples 1 to 7

Two grades of ALC were tested during these tests:

- an ALC described as "standard", comprising 2.7 g of 1,5-hexadiene/kg
- an ALC described as "high purity", comprising 180 ppm of 1,5-hexadiene.

In Examples 1 and 2, the epoxidation was carried out at a temperature of 35°C, an ALC/H₂O₂ molar ratio of 2 mol/mol and a CH₃OH/ALC molar ratio of 7.8 mol/mol. The results in terms of degree of conversion are given in Table 1.

Table 1

Time (h)	H ₂ O ₂ Degree of conversion (%)	
	Example 1 "standard" ALC	Example 2 "high purity" ALC
6	75.7	84.4
27	26.8	44.7
100		28.3
147		25.1

In Examples 3 and 4, the epoxidation was carried out at a temperature of 55°C, an ALC/H₂O₂ molar ratio of 2 mol/mol and a CH₃OH/ALC molar ratio of 7.8 mol/mol. The results in terms of degree of conversion are given in Table 2.

Table 2

Time (h)	H ₂ O ₂ Degree of conversion (%)	
	Example 3 "standard" ALC	Example 4 "high purity" ALC
6	89.0	93.9
27	67.5	79.2
120	33.0	54.2
292		41.0

In Examples 5 to 7, the epoxidation was carried out at a temperature of 55°C, an ALC/H₂O₂ molar ratio of 5 mol/mol and a CH₃OH/ALC molar ratio of

2.1 mol/mol. In Example 7, with conditions identical to Examples 5 and 6, a "high purity" ALC was employed and, at the same time, the reactor was fed with 1,5-hexadiene so that the total flow rate of 1,5-hexadiene ("high purity" ALC + addition) is identical to that of an example with "standard" ALC. The results in terms of degree of conversion are given in Table 3.

Table 3

Time (h)	H ₂ O ₂ Degree of conversion (%)		
	Example 5 "standard" ALC	Example 6 "high purity" ALC	Example 7 "high purity" ALC + 1,5-hexadiene
6	92.2	96.0	94.5
27	70.7	94.0	80.2
101	27.2	79.4	
120	25.0	75.0	37.6
194		68.4	

A rapid deactivation is observed in Example 7, although slightly less marked than in Example 5 with a "standard" ALC. The conversion of the H₂O₂ after 120 h, equal to 37.6%, was markedly lower than that observed with "high purity" ALC low in 1,5-hexadiene (75%) and slightly greater than that observed with a "standard" ALC (25%). The presence of greater amounts of 1,5-hexadiene in the "standard" ALC might therefore largely explain the effect observed. The higher conversion than that observed with the "standard" ALC nevertheless indicates that other impurities (1,4-hexadiene, methylcyclopentene, and the like) might also influence the rate of deactivation.

CLAIMS

1. Process for the manufacture of 1,2-epoxy-3-chloropropane by reaction between allyl chloride and hydrogen peroxide in the presence of a catalyst and in the possible presence of at least one solvent, characterized in that the allyl chloride employed comprises less than 2000 ppm by weight of 1,5-hexadiene.
5
2. Process according to Claim 1, characterized in that the allyl chloride employed comprises less than 1000 ppm by weight of 1,5-hexadiene.
3. Process according to Claim 2, characterized in that the allyl chloride employed comprises less than 200 ppm by weight of 1,5-hexadiene.
- 10 4. Process according to any one of Claims 1 to 3, characterized in that the reaction is carried out at a temperature from 45 to 80°C.
5. Process according to any one of Claims 1 to 4, characterized in that the reaction is carried out at a pH maintained at a value from 3 to 4.5.
- 15 6. Process according to any one of Claims 1 to 5, characterized in that the amounts of allyl chloride and hydrogen peroxide employed are such that their molar ratio is from 2 to 7.
7. Process according to any one of Claims 1 to 6, characterized in that the solvent comprises methanol.
- 20 8. Process according to any one of Claims 1 to 7, characterized in that the catalyst comprises TS-1.
9. Process according to any one of Claims 1 to 8, characterized in that the catalyst is present in the form of a fluid bed.
- 25 10. Process according to any one of Claims 1 to 9, characterized in that the reaction is carried out in a reactor of loop type comprising recirculation of the epoxidation medium.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/JP03/12519

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 C07D301/12 C07D303/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 C07D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

PAJ, EPO-Internal, WPI Data, CHEM ABS Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 017, no. 167 (C-1043), 31 March 1993 (1993-03-31) - & JP 04 327582 A (MITSUI TOATSU CHEM INC), 17 November 1992 (1992-11-17) Tables 1 and 3 abstract	1-10
A	EP 0 568 336 A (ARCO CHEM TECH) 3 November 1993 (1993-11-03) Claims 1,4,5,10,12; example 7	1-10



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

B document member of the same patent family

Date of the actual completion of the international search

30 January 2004

Date of mailing of the international search report

19/02/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Kirsch, C

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/93/12519

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 04327582	A	17-11-1992	NONE	
EP 0568336	A	03-11-1993	US 5262550 A	16-11-1993
			AT 129708 T	15-11-1995
			DE 69300720 D1	07-12-1995
			DE 69300720 T2	11-04-1996
			EP 0568336 A2	03-11-1993
			ES 2079236 T3	01-01-1996
			JP 6009592 A	18-01-1994